

Blox, Angled Ceiling Clouds

Premier Collection


Pacify problematic sound by beautifully boxing up the racket. An angled insert creates visual movement with help from a range of cloud sizes, lighting, and color. Blox ceiling clouds offer a fresh take on noise reduction, inviting you to customize your space with Premier colors from subtle to bold shades, realistic WoodGrain patterns, or your own combination inside and out. Blox puts total creativity in your hands.

Specifications

Surface	Ceiling
Material	FilaSorb™ polyester felt
Weight	0.49 lb./ft ² (±10%)
Standard Sizes	Width: 20" up to 44" W (2" increments) Length: 20" up to 44" L (2" increments) Height: 10" up to 20" H (2" increments)



Blox, Angled Ceiling Cloud in Valentine, Quartz, and Umber



Blox, Angled Ceiling Cloud in Valentine

* Any lighting depicted in renderings is for illustrative purposes only and is not included with the product. All lighting must be specified and coordinated by the project lighting designer or electrical engineer.

Technical

NRC Rating	Pending product testing
Fire Test	ASTM E84, Class A CAN/ULC-S102 Flame spread index: 15 Smoke developed index: 200
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

Details

Lead Time	3 – 6 weeks
Origin	Manufactured and assembled in the US
Warranty	Product: 20 years* Colorfastness: 20 years*

* Conditions apply

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m ³
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

* PET is recyclable through participating partners



For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call **800.966.8557**.


Blox, Angled Ceiling Clouds | January 2026

Colorways

PREMIER

							
White WH12	Milkyway MI74	Ivory IV11	Pearl PE21	Valentine VA70	Quartz QU67	Stonewash ST72	Sea Salt SE57
							
Platinum PL04	Almond AL55	Pistachio PI25	Turmeric TU60	Flamingo FL61	Amethyst AM69	Periwinkle PE23	Peacock PE20
							
Metal ME03	Mushroom MU75	Celery CE65	Wheat WH68	Peach PE19	Lilac LI13	Marine MA15	Sencha SE58
							
Grey GR02	Umber UM54	Wasabi WA29	Popcorn PO26	Currant CU59	Berry BE06	Azure AZ05	Oregano OR18
							
Charcoal CH01	Walnut WA56	Eucalyptus EU71	Carrot CA08	Loganberry LO77	Granite GR62	Denim DE09	Kale KA12
							
Piano Black PI24	Slate SL27	Nori NO76	Peppercorn PE22	Shiraz SH63	Flint FL64	Midnight MI16	

Order samples at acoufelt.com/colorways

 For questions or additional product information, visit acoufelt.com or call 800.966.8557.

Blox, Angled Ceiling Clouds | January 2026



Sizes

Standard Width: 20" up to 44" W (2" increments)



Standard Height: 10" up to 20" H (2" increments)

Standard Length: 20" up to 44" L (2" increments)



Plan



Elevations





Perspective



Hardware Spacing

20, 22" W	10" on center spacing
24, 26, 28, 30" W	12" on center spacing
32, 34, 36, 38" W	16" on center spacing
40, 42, 44" W	20" on center spacing

20, 22" W	10" on center spacing
24, 26, 28, 30" W	12" on center spacing
32, 34, 36, 38" W	16" on center spacing
40, 42, 44" W	20" on center spacing



How to Specify

1. Choose Sizes

2. Choose Colorways

Blox sizes and shapes can be mixed to create desired design. See Blox, Deep and Shallow specification sheets for additional information.


1. Choose Sizes

2. Choose Colorways

Select one or multiple colorways to achieve the overall desired design. See colorway choices on page 3.


Mounting Methods

Cable to deck




Hardware Kits:
 HK1006 - 48" Cable
 HK1010 - 120" Cable

Swivel cable to deck




Hardware Kits:
 HK1007 - 48" Cable
 HK1011 - 120" Cable

Cable to strut channel




Hardware Kits:
 HK1009 - 48" Cable
 HK1013 - 120" Cable

Threaded rod




Hardware Kits:
 HK1014 - 24" Cable
 HK1015 - 48" Cable

Threaded rod to strut channel



Hardware Kits:
 HK1277 - 24" Cable
 HK1278 - 48" Cable


Direct to strut channel



Hardware Kits:
 HK1016

Acoustic Performance

Test Method	ASTM E795-16
Install Method	J-600
Rating Method	ASTM C423-17
Mounting Method	Sample tested 5 baffles 110" L x 12" D x 3" thickness, hanging 600mm from floor and 152mm from each other
Test Results	Pending product testing




Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
12mm	Pending product testing						

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.

 For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call **800.966.8557**.

Blox, Angled Ceiling Clouds | January 2026