




Interlace, Crisscross Ceiling Clouds

Premier Collection

Interlace Ceiling Clouds is a suspended, acoustic installation featuring refined, entwined patterns designed to complement open interiors. Crisscross design's subtle, dynamic form provides architectural depth while offering the functional benefit of enhanced sound absorption, making it an ideal solution for improving acoustics and ambiance across any space.

Specifications

Surface	Ceiling
Material	FilaSorb™ polyester felt
Weight	0.49 lb./ft ² (±10%)
Standard Sizes	Heights: 6" up to 12" H (2" increments) Widths: 48, 60, 72, 96, 108" W Lengths: 48, 60, 72, 96, 108" L



Interlace, Crisscross Ceiling Clouds in Azure

Technical

NRC Rating	0.85, 200mm air gap* 0.80, 400mm air gap*
Fire Test	ASTM E84, Class A CAN/ULC-S102 Flame spread index: 15 Smoke developed index: 200
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

* Test results available upon request

Details

Lead Time	3 - 6 weeks
Origin	Manufactured and assembled in the US
Warranty	Product: 20 years* Colorfastness: 20 years*

* Conditions apply

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m ³
Recyclable	100%*
Certifications	Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

* PET is recyclable through participating partners



For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call 800.966.8557.

Interlace, Crisscross Ceiling Clouds | January 2026

Colorways

PREMIER



White
WH12



Milkyway
MI74



Ivory
IV11



Pearl
PE21



Valentine
VA70




Quartz
QU67



Stonewash
ST72



Sea Salt
SE57



Platinum
PL04




Almond
AL55



Pistachio
PI25



Turmeric
TU60



Flamingo
FL61




Amethyst
AM69



Periwinkle
PE23



Peacock
PE20



Metal
ME03



Mushroom
MU75



Celery
CE65



Wheat
WH68



Peach
PE19



Lilac
LI13



Marine
MA15




Sencha
SE58



Grey
GR02



Umber
UM54



Wasabi
WA29



Popcorn
PO26



Currant
CU59



Berry
BE06



Azure
AZ05



Oregano
OR18




Charcoal
CH01




Walnut
WA56



Eucalyptus
EU71




Carrot
CA08



Loganberry
LO77




Granite
GR62



Denim
DE09




Kale
KA12




Piano Black
PI24




Slate
SL27




Nori
NO76




Peppercorn
PE22



Shiraz
SH63



Flint
FL64



Midnight
MI16

Order samples at acoufelt.com/colorways




For questions or additional product information,
visit acoufelt.com or call 800.966.8557.

Interlace, Crisscross Ceiling Clouds | January 2026


Sizes

Standard Sizes Heights: 6" up to 12" H (2" increments)
 Widths: 48, 60, 72, 96, 108" W
 Lengths: 48, 60, 72, 96, 108" L



Perspective



Plan




Elevations




Mounting Methods

Cable to deck




Hardware Kits:
 HK1006 - 48" Cable
 HK1010 - 120" Cable

Cable to T-grid




Hardware Kits:
 HK1008 - 48" Cable
 HK1012 - 120" Cable

Cable to strut channel



Hardware Kits:
 HK1009 - 48" Cable
 HK1013 - 120" Cable


Swivel cable to deck



Hardware Kits:
 HK1007 - 48" Cable
 HK1011 - 120" Cable

Acoustic Performance

Test Method	ISO 11654-2002
Install Method	E200, E400
Rating Method	ASTM C423-09a
Test Results	NRC 0.85, 200mm air gap SAA 0.86, 200mm air gap NRC 0.80, 400mm air gap SAA 0.83, 400mm air gap




	Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
	12mm, 200mm air gap	0.40	0.75	0.90	0.85	0.95	1.00	0.85
	12mm, 400mm air gap	0.55	0.75	0.70	0.90	0.95	1.00	0.80

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one-third octave bands at 125, 250, 500, 1000, 2000, and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the 12 one-third octave bands ranging between 200 and 2500 Hz.

 For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call **800.966.8557**.

Interlace, Crisscross Ceiling Clouds | January 2026