



SoftenUp, Ridge Ceiling Frames

Premier Collection

SoftenUp™ modular ceiling frames add warmth and sophistication to any environment. The Ridge frames features a larger slat profile than its Plateau counterpart, offering a bold yet minimalist aesthetic. Designed for exceptional acoustic performance and seamless integration into standard T-grid drop-ceiling systems. Ridge frames are available in a range of sizes and colors, giving you the freedom to create dynamic, customized ceiling designs.

Specifications

Surface	Ceiling	
Material	FilaSorb™ polyester felt	
Weight	0.49 lb./ft ² (±10%)	
Standard Sizes	Height: 3" up to 6" H Thickness: 1" up to 5" T Backer Panels: 24" W x 24" L 24" W x 48" L 24" W x 96" L	
Compatible T-grid	Type 9/16" Flat 15/16" Flat	Layout Standard 24" x 24" Standard 24" x 24"



SoftenUp, Ridge Ceiling Frames in Almond

Technical

NRC Rating	0.95*
Fire Test	ASTM E84, Class A CAN/ULC-S102 Flame spread index: 15 Smoke developed index: 200
Water Sorption	ASTM C1104-2019 (A Modified) Water sorbed by weight: 0.20% (based on a 12mm thick panel)
Colorfastness	ISO 105-B02, 6-7

* Test results available upon request

Details

Lead Time	3 - 6 weeks
Origin	Manufactured and assembled in the US
Warranty	Product: 20 years* Colorfastness: 20 years*

* Conditions apply

Environmental

Recycled Content	Minimum 60%
Energy	Generated using 40% solar energy
Indoor Air Quality	VOC less than/equal to 0.5mg/m ³
Recyclable	100%*
Certifications	Environmental Product Declaration Declare Certification - LBC Red List Free (third-party verified) SCS Global Indoor Advantage Gold

* PET is recyclable through participating partners



For questions or additional product information, visit acoufelt.com or call **800.966.8557**.

SoftenUp, Ridge Ceiling Frames | January 2026

Colorways

PREMIER



White
WH12



Milkyway
MI74



Ivory
IV11



Pearl
PE21



Valentine
VA70



Quartz
QU67



Stonewash
ST72



Sea Salt
SE57




Platinum
PL04



Almond
AL55



Pistachio
PI25



Turmeric
TU60



Flamingo
FL61



Amethyst
AM69



Periwinkle
PE23



Peacock
PE20



Metal
ME03



Mushroom
MU75




Celery
CE65



Wheat
WH68



Peach
PE19



Lilac
LI13



Marine
MA15



Sencha
SE58




Grey
GR02




Umber
UM54



Wasabi
WA29



Popcorn
PO26



Currant
CU59



Berry
BE06



Azure
AZ05



Oregano
OR18




Charcoal
CH01




Walnut
WA56




Eucalyptus
EU71




Carrot
CA08



Loganberry
LO77



Granite
GR62



Denim
DE09



Kale
KA12




Piano Black
PI24




Slate
SL27




Nori
NO76




Peppercorn
PE22



Shiraz
SH63



Flint
FL64



Midnight
MI16

Order samples at acoufelt.com/colorways



For questions or additional product information,
visit acoufelt.com or call 800.966.8557.

SoftenUp, Ridge Ceiling Frames | January 2026

How to Specify

1. Choose Slat Size & Clearance


2. Choose Backer Panel Size

3. Choose Colorways

4. Optional Corner Panel

Slats are available in a range of thicknesses, heights, and clearances. Select the desired combination from the following:

Thickness	Height	Clearance	Thickness	Height	Clearance
1"	3"	2"	3"	3"	3"
1"	3"	3"	3"	4"	3"
1"	4"	2"	3"	5"	3"
1"	4"	3"	3"	6"	3"
1"	5"	2"	4"	3"	2"
1"	5"	3"	4"	4"	2"
1"	6"	2"	4"	5"	2"
1"	6"	3"	4"	6"	2"
2"	3"	2"	5"	3"	1"
2"	3"	4"	5"	3"	3"
2"	4"	2"	5"	4"	1"
2"	4"	4"	5"	4"	3"
2"	5"	2"	5"	5"	1"
2"	5"	4"	5"	5"	3"
2"	6"	2"	5"	6"	1"
2"	6"	4"	5"	6"	3"




1. Choose Slat Size & Clearance

2. Choose Backer Panel Size

3. Choose Colorways

4. Optional Corner Panel

Backer panels are available in three lengths.



Clip spacing may differ. Product ships assembled.
Safety cable comes standard on all SoftenUp™ product lines. See installation guides for additional details.

For questions or additional product information, visit acoufelt.com or call 800.966.8557.

SoftenUp, Ridge Ceiling Frames | January 2026

How to Specify (cont.)

1. Choose Slat Size

2. Choose Backer Panel Size

3. Choose Colorways


4. Optional Corner Panel

Select one colorway for your slats and one colorway for your backer panel.
See colorway choices on page 3.

If you're specifying dark colored backer panels, we recommend dark drop ceiling grids (not provided).

Backer panel
Select one colorway

Slats
Select one colorway




1. Choose Slat Size

2. Choose Backer Panel Size

3. Choose Colorways


4. Optional Corner Panel

SoftenUp acoustical ceiling panels can be seamlessly integrated with corresponding wall panels by specifying the corresponding corner piece.



Ceiling corner panel

Wall panel



See corresponding SoftenUp™, Ridge wall panel specification sheet for additional information.




For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call 800.966.8557.


SoftenUp, Ridge Ceiling Frames | January 2026

Recommended Layouts


Layout 1




Layout 2



Layout 3




Layout 4




Lighting Coordination


24" x 24", 24" x 48" Grid light




Drop pendant light



Recessed light




Grid mounted light (track, pendant)



Acoustic Performance

Test Method	ASTM E795
Install Method	Type E-400
Rating Method	ASTM C423
Mounting Method	2" T x 3" H slat on 12mm backer with 400mm air gap
Test Results	NRC 0.95 SAA 0.96




Frequency f (Hz)	125	250	500	1000	2000	4000	NRC
12mm	0.67	0.86	0.96	1.02	1.04	1.00	0.95

What is a Noise Reduction Coefficient (NRC)?

You'll find the NRC rating in the specifications of all of our products. This acronym stands for Noise Reduction Coefficient, and is expressed as a single number, a rating that describes the degree to which acoustic products can absorb sound.

You can use NRC values to understand the overall performance of our acoustic wall and ceiling products. The higher the NRC, the better the product is at soaking up the sound.

Performance Indices: Noise Reduction Coefficient (NRC) results represent the absorption coefficients measured at the one third octave bands at 125, 250, 500, 1000, 2000 and 4000 Hz rounded to the nearest 0.05. Acoustic testing has been performed according to the methods mentioned above. Customization of installation of the product could alter the results. Sound Absorption Average (SAA) indicates the absorption coefficient average for the twelve one-third octave bands ranging between 200 and 2500 Hz.

 For questions or additional product information, visit [acoufelt.com](https://www.acoufelt.com) or call **800.966.8557**.

SoftenUp, Ridge Ceiling Frames | January 2026

Suspension

The SoftenUp ceiling tiles are designed to connect to standard drop-ceiling grid systems via a series of tabs integrated into the design. No additional hardware is required for standard installation. Seismic zones may require additional considerations (see note on seismic).

Life Safety

The panels can be trimmed on-site, using a sharp utility knife, to accommodate any existing signage and/or wayfinding markings. Cut-outs must occur in 2" gap between slats. All fixtures must be supported independent of tiles.

** Panels cut on-site may require additional support.*

Weight

- 3"H slat weight = 2 lbs./sq. ft.
- 1"H slat weight = 1.25 lbs./sq. ft.

Clearance/Tolerance

When installed, SoftenUp tiles have a consistent 1/8" reveal to account for any on-site tolerance concerns. Panels have a method for tile alignment integrated into the design.

** A continuous slat design is available. Contact us for details.*

MEP/FP

The panels can be trimmed on-site, using a sharp utility knife, to accommodate any MEP/FP fixtures. These include, but are not limited to, drop-in lighting and diffusers, recessed lighting, linear diffusers, concealed and exposed fire sprinklers, and A/V equipment. Please consult all local and municipal codes, as well as a licensed engineer, for full compliance requirements. Cut-outs must occur in 2" gap between slats. All fixtures must be supported independent of tiles.

**Panels cut on-site may require additional support.*

Ceiling Access

Panels with an integrated folding access tab are available upon request. These folding tabs allow for the removal of individual tiles to access ceiling systems.

Seismic

SoftenUp ceiling tiles can provide seismic compliance through a mechanical direct screw attachment through the panel to the grid system, or an individual tile off to building structure. Please consult all local and municipal codes, as well as a licensed engineer, for full compliance requirements.

